

VENSTAR®

FLATSTAT THERMOSTAT

COMMERCIAL THERMOSTAT SERIES



2.7" w x 4.3" h x .37"

**ELEGANT AND UNOBTRUSIVE,
THIS FLAT TO THE WALL
ARCHITECTURAL DESIGN
OFFERS MANY HIGH TECH
FEATURES AND A LARGE, EASY
TO READ DISPLAY WITH A
CONTINUOUS BACKLIGHT.**



STANDARD FEATURES

- One for All 2-stage heat, 2-stage cool for use with gas/electrics, heat pumps, electric & hydronic heat
- Autochangeover - automatically switches between heating and cooling as needed
- Thermostat-locking - set points can be adjusted only by authorized individuals when this feature is on
- All programming and set points stored in non-volatile memory and are never lost in a power failure
- LED indicator glows green or red to indicate cooling or heating
- Mounting bracket included for easy drywall installation, or fits in 2" x 4" junction box.

Security cover included.



**MODEL:
T2300FS**

MODEL T2300FS

- 7-day programmable
- Accepts the optional outdoor air temperature sensor or optional indoor remote temperature sensor
- Up to 3 occupied periods for commercial installations
- 3 security levels with set point limiting
- Override up to 4 hours
- Preoccupancy fan purge
- Battery backup for clock (12 hours)
- Includes on board dry contact terminals